

Turn your dream into reality



TU2200



TU2500L



TTU2700/5

The *classic* American line

7'
6'
5'
4'



TU1000	TU1450/1 TU1450T/1	TU2200 TU2200T	TU2200/1 TU2200T/1	TU2500L TU2500LT	TU2700/4 XL	TTU2700	TTU2700/75 XL TTU2700/5	TLU2000/91 TLU2000/93	TLU2450/1
B \$6,050 T \$7,500	B \$7,950 T \$8,350	B \$8,350 T \$8,750	B \$11,250 T \$12,650	B \$15,450 T \$16,700	T \$11,950	T \$13,950	T \$14,950 T \$16,350	B \$12,950 B \$13,350	B \$16,450

Warm regards,





Classic American line

Technical Information		Retail Price	Weight	Footprint		Firebox		Wood Length	Load per Firing	Maximum Heat Output*
				Width	Depth	W	D			
		USD	lb	in.	in.	in.	in.	in.	lb	Btu
Small Models										
TU1000	4' height, base vent	\$6,050	2,340	33.1	18.9	12.2	9.6	10-11	19	10,000
TU1000T	5' height, top vent	\$7,500	2,980	33.1	18.9	12.2	9.6	10-11	24	12,500
TU1450/1	5' 3" height, base vent	\$7,950	2,940	35.4	18.9	12.2	9.6	10-11	24	12,000
TU1450T/1	5' 3" height, top vent	\$8,350	2,940	35.4	18.9	12.2	9.6	10-11	24	12,000
Mid-Sized Models										
TU2200	5' height, base vent	\$8,350	3,900	40.2	23.6	15.7	14.4	14-15	31	16,500
TU2200T	5' height, top vent	\$8,750	3,960	40.2	23.6	15.7	14.4	14-15	32	16,000
TU2200/1	5' height, base vent, rough stones	\$11,250	4,570	40.2	23.6	15.7	14.4	14-15	37	19,500
TU2200T/1	5' height, top vent, rough stones	\$12,650	4,570	40.2	23.6	15.7	14.4	14-15	37	18,500
TU2200T/51	6' height, top vent	\$10,250	4,660	40.2	23.6	15.7	14.4	14-15	37	19,000
TU2500L	6' height, base vent, rough stones	\$15,450	5,380	40.2	23.6	15.7	14.4	14-15	43	22,000
TU2500LT	6' height, top vent, rough stones	\$16,700	5,380	40.2	23.6	15.7	14.4	14-15	43	22,000
TLU2000/91	5' 5" height, 15.4" x 18.3" bakeoven, base vent	\$12,950	4,580	36.6	29.5	14.4	12.0	12-13	37	19,500
TLU2000/93	5' 5" height, 15.4" x 18.3" rear-facing bakeoven, base vent	\$13,350	4,760	36.6	29.5	14.4	12.0	12-13	38	20,000
Large Models										
TTU2700/4 XL	6' height, top vent	\$11,950	5,970	40.2	29.5	15.7	19.7	14-18	48	23,000
TTU2700/75 XL	7' height, 16.5" x 17.1" bakeoven, top vent	\$14,950	6,710	40.2	29.5	15.7	19.7	14-18	54	26,000
TTU2700	7' height, see-through firebox, top vent	\$13,950	6,540	40.2	29.5	15.7	24.8	14-18	52	25,000
TTU2700/5	7' height, see-through firebox, 16.5" x 17.1" bakeoven, top vent	\$16,350	7,200	40.2	29.5	15.7	24.8	14-18	58	28,000
TLU2450/1	5' 6" height, 17.7" x 21.9" bakeoven, base vent	\$16,450	6,600	42.5	35.4	15.7	14.4	14-15	53	26,000

***Maximum heat output is based on two firings per day, at least 10 hours apart.**

Delivery and on-site assembling are not included in the Retail Price. Heat shields, hearth tiles, benches & other accessories are available as optional features. Tulikivi heaters are high thermal mass appliances and require appropriate structural support. Being a naturally occurring material, soapstone can vary in aspect and weight. 5 years Warranty. Tulikivi heaters must be assembled on site by a Tulikivi installer. They are UL/ULC safety tested & listed and don't require EPA certification. Chimney: 20' minimum height from floor for models with bakeovens, 15' otherwise. Recommended flue dia.: 6" or 7" for small models, 7" or 8" otherwise. Clearances to combustibles: 20" to back, 14" to sides, 10" to top and 48" to front. Those can be reduced to 3" with a Tulikivi specified heat shield. Floor protection: 3/8" min. thickness of non-combustible material, extending 8" from sides, 8" from back (unless a heat shield is used) and 16" from front of the heater.

