

Turn your dream into reality



TU1000/92



TU2200/50 GRAFIA



TLU2450/92

The modern American line



Heater Models without Grafia Surface Treatment.

- B \$6,300 TU1000/50
- T \$7,900 TU1000T/50
- B \$8,700 TU2200/50
- T \$8,950 TU2200T/50
- B \$11,450 TLU2000/50

Warm regards,





Modern American line

Technical Information		Retail Price	Weight	Footprint		Firebox		Wood Length	Load per Firing	Maximum Heat Output*
				Width	Depth	W	D			
		USD	lb	in.	in.	in.	in.	in.	lb	Btu
Small Models										
TU1000/50 Grafia	4' height, base vent, Grafia texture	\$6,600	2,200	33.1	18.9	12.2	9.6	10-11	18	9,500
TU1000T/50 Grafia	5' height, top vent, Grafia texture	\$8,200	2,880	33.1	18.9	12.2	9.6	10-11	23	12,000
TU1000/92	5' height, base vent	\$7,600	2,690	33.1	18.9	12.2	9.6	10-11	22	11,000
TU1000T/92	5' height, top vent	\$7,950	2,880	33.1	18.9	12.2	9.6	10-11	23	12,000
Mid-Sized Models										
TU2200/92	5' height, base vent	\$8,500	3,900	40.2	23.6	15.7	14.4	14-15	31	16,500
TU2200T/92	5' height, top vent	\$9,250	4,090	40.2	23.6	15.7	14.4	14-15	33	16,500
TU2200/50 Grafia	5' height, base vent, Grafia texture	\$9,200	3,980	40.2	23.6	15.7	14.4	14-15	32	17,000
TU2200T/50 Grafia	5' height, top vent, Grafia texture	\$9,450	3,980	40.2	23.6	15.7	14.4	14-15	32	16,500
TLU2000/92	5' 5" height, 15.4" x 18.3" bakeoven, base vent	\$11,850	4,320	36.6	27.2	14.5	12.0	12-13	35	18,500
TLU2000/94	5' 5" height, 15.4" x 18.3" rear-facing bakeoven, base vent	\$12,150	4,340	36.6	27.2	14.5	12.0	12-13	35	18,500
TLU2000/50 Grafia	5' 5" height, 15.4" x 18.3" bakeoven, base vent, Grafia texture	\$11,950	4,300	36.6	27.2	14.5	12.0	12-13	34	18,000
Large Models										
TTU2700/8 XL	6' height, top vent	\$11,950	6,140	40.2	29.5	15.7	19.7	14-18	49	24,000
TLU2450/92	5' 6" height, 17.7" x 21.9" bakeoven, base vent	\$14,550	5,730	42.5	35.4	15.7	14.4	14-15	46	22,500

*Maximum heat output is based on two firings per day, at least 10 hours apart.

Delivery and on-site assembling are not included in the Retail Price. Heat shields, hearth tiles, benches & other accessories are available as optional features.

Tulikivi heaters are high thermal mass appliances and require appropriate structural support. Being a naturally occurring material, soapstone can vary in aspect and weight.

5 years Warranty. Tulikivi heaters must be assembled on site by a Tulikivi installer. They are UL/ULC safety tested & listed and don't require EPA certification.

Chimney: 20' minimum height from floor for models with bakeovens, 15' otherwise. Recommended flue dia.: 6" or 7" for small models, 7" or 8" otherwise.

Clearances to combustibles: 20" to back, 14" to sides, 10" to top and 48" to front. Those can be reduced to 3" with a Tulikivi specified heat shield.

Floor protection: 3/8" min. thickness of non-combustible material, extending 8" from sides, 8" from back (unless a heat shield)

